



Aluminium slot ventilator

Specific Benefits

- T-bar deflects air up and down
- Compression closing action
- For use on 13mm slot
- Use with external canopy or plastic grille
- 2000mm² or 4000mm² versions
- Based on successful Trimvent principle
- Unique linkages ensure constant friction and smooth action
- Vent supplied with screw covers
- Patented and registered design
- Special colours available on request
- Cord control vent available
- Sleeve for hollow profiles available
- Felted gasket for increased performance

Manufactured From

Vent & Canopy - Aluminium 6063 HIT T6, component parts - POM + PP (UV stable)

Grille - PP (UV stable)

Recommended Screws

Vent & Canopy - No.6 Round Head

Grille - Pins (supplied if requested)

Airflow

TV4000

2 Pa = 5.8m³/hr @ STP

5 Pa = 13.1m³/hr @ STP

10 Pa = 22.6m³/hr @ STP

Acoustic Properties

Details on request

Specifiers Text

Go to www.titon.com/spectext or available on request

Standards

Tested in accordance with BS 6375 Part 1 - 1989

"Performance of windows - classification for weathertightness"

Full test results available on request

Details

Product	Code	L	W	P* Closed-Open	Slot Size
TV 2000 Vent	TA4002	255	17	16.5-22.5	223 x 13
TV 2000 Canopy	TA4006	255	28	21	223 x 13
TV 2000 Grille	TA4011	255	19	1 +12 recessed	223 x 13
TV 4000 Vent	TA4001	400	17	16.5-22.5	173.5 + 20 + 173.5 x 13
TV 4000 Canopy	TA4005	400	28	21	173.5 + 20 + 173.5 x 13
TV 4000 Grille	TA4010	400	19	1 +12 recessed	173.5 + 20 + 173.5 x 13

P* dimension - add 11.5 for overall vent depth



Trimvent 4000 ventilator



Through sash with canopy

